References:

[1] Alexandros G. Fragkiadakis, Elias Z. Tragos, Ioannis G. Askoxylakis, (2012) “A Survey on Security Threats and Detection Techniques in Cognitive Radio Networks”, IEEE Communications Surveys & Tutorials, 15, 1, 1553-877X.

[2] Ali Al-Talabani, Yansha Deng, A. Nallanathan and Huan X. Nguyen, (2015) “Enhancing Secrecy Rate in Cognitive Radio Networks via Multi-level Stackelberg Game”, 1089-7798.

[3] Amr A. El-Sherif, and Amr Mohamed, (2014) “Joint Routing and Resource Allocation for Delay Minimization in Cognitive Radio Based Mesh Networks”, IEEE Transactions on Wireless Communications, 13, 1, 1558-2248.

[4] Anthony Busson, Bijan Jabbari, Alireza Babaei, and V´eronique V`eque, (2014) “Interference and Throughput in Spectrum Sensing Cognitive Radio Networks using Point Processes”, Journal of Communications and Networks, 16, 1, 1976-5541.

[5] Ayaz Ahmad, Sadiq Ahmad, Mubashir Husain Rehmani and Naveed Ul Hassan, (2015)” A Survey on Radio Resource Allocation in Cognitive Radio Sensor Networks”, IEEE, 1553-877X.

[6] C. Liang and F. R. Yu, (2015) "Wireless Network Virtualization: A Survey, Some Research Issues and Challenges" IEEE Communication Surveys & Tutorials,17, 1, 358-380, 1553-877X.

[7] Georgios I. Tsiropoulos, Octavia A. Dobre, Mohamed H. Ahmed, and Kareem E. Baddour, (2013) “Radio Resource Allocation Techniques for Efficient Spectrum Access in Cognitive Radio Networks”, 1553-877X.

[8] Himanshu Agrawal, “Spectrum Allocation in Cognitive Networks”, JIIT-128 NOIDA, India.

[9] Huijin Cao, Hongqiao Tian, Jun Cai, Attahiru S. Alfa, Shiwei Huang, (2016) “Dynamic Load-balancing Spectrum Decision for Heterogeneous Services Provisioning in Mutil-channel Cognitive Radio Networks”, IEEE, 1536-1276.

[10] Hurtado Borràs, J. Palà Solé, D. Camps Mur and S. Sallent Ribes, (2015) "SDN Wireless Backhauling for Small Cells" in IEEE ICC 2015 - Mobile and Wireless Networking Symposium, Electronic ISBN: 978-1-4673-6432-4.

[11] Hyungsik Ju, and Rui Zhang, (2014) “Throughput Maximization in Wireless Powered Communication Networks”, IEEE transactions on wireless communications, 1536-1276.

[12] Jian Yang, and Hangsheng Zhao, (2015) “Enhanced Throughput of Cognitive Radio Networks by Imperfect Spectrum Prediction”, IEEE Communications Letters,19, 10, 1089-7798.

[13] Junni Zou, Qiong Wu, Hongkai Xiong, Chang Wen Chen, (2015) “Dynamic Spectrum Access and Power Allocation for Cooperative Cognitive Radio Networks”, 2015 IEEE, 1053-587X.

[14] James Neel, R. Michael Buehrer, Robert P. Gilles, (2002) “Game Theoretic Analysis of A Network Of Cognitive Radios”,IEEE.

[15] Lei Xu IEEE Member, A. Nallanathan IEEE Fellow, Xiaofei Pan, Jian Yang IAPR Fellow, and Wenhe Liao, (2018) “Security-Aware Resource Allocation with Delay Constraint for NOMA-based Cognitive Radio Network”, IEEE Transactions on Information Forensics and Security, 1556-6013.

[16] LI Hongning, PEI Qingqi, MA Lichuan, (2014) “Channel Selection Information Hiding Scheme for Tracking User Attack in Cognitive Radio Networks”, China Communications,1673-5447.

[17] Li Jianwu1, Feng Zebing2, Feng Zhiyong2, Zhang Ping1, (2015) “A Survey of Security Issues in Cognitive Radio Networks”, China Communications • March, 1673-5447.

[18] Long Yang, Hai Jiang, Sergiy A. Vorobyov, Jian Chen and Hailin Zhang, (2015) “Secure Communications in Underlay Cognitive Radio Networks: User Scheduling and Performance Analysis”, IEEE Communications Letters, IEEE, 1089-7798.

[19] Mahmoud Khasawneh, Anjali Agarwal, (2017) “A Secure and Efficient Authentication Mechanism Applied to Cognitive Radio Networks”, IEEE, 2169-3536.

[20] Minho Jo, Longzhe Han, Dohoon Kim, and Hoh Peter In, Korea University, (2013) “Selfish Attacks and Detection in Cognitive Radio Ad-Hoc Network”, IEEE Network , 0890-8044.

[21] Mohd Adib Sarijari1, Mohd Sharil Abdullah, Gerard JM Janssen and Alle-Jan

van der Veen, (2015) “On achieving network throughput demand in cognitive radio-based home area networks”, EURASIP Journal on Wireless Communications and Networking.

[22] Pham Viet Tuan and Insoo Koo, (2015) “Throughput Maximization for Secondary User under Battery Imperfections in Cognitive Radio Networks”, IEEE, 1530-437X.

[23] Qiang Li1, Ashish Pandharipande2, See Ho Ting3 and Xiaohu Ge1, (2015) “Spectrum sharing on interference channels with a cognitive relay”, Li et al. EURASIP Journal on Wireless Communications and Networking.

[24] Riheng Jia, Kechen Zheng, Jinbei Zhang, Luoyi Fu, Pengyuan Du, Xinbing Wang, and Jun Xu, (2014) “Asymptotic Analysis on Throughput and Delayin Cognitive Social Networks”, IEEE Transactions on Communications, 62, 8, 1558-0857.

[25] Rui Zhang, Ying-Chang Liang, and Shuguang Cui, (2010) “Dynamic Resource Allocation in Cognitive Radio Networks: A Convex Optimization Perspective”, 1053-5888.

[26] Seunghyun Lee and Rui Zhang, (2015) “Cognitive Wireless Powered Network: Spectrum Sharing Models and Throughput Maximization”, IEEE, 2332-7731.

[27] Shi-Qi Liu and Bin-Jie Hu, (2014) “Analysis of Sensing Efficiency for Cooperative Spectrum Sensing with Malicious Users in Cognitive Radio Networks”, IEEE Communications Letters, 18, 9, 1558-2558.

[28] Shiyin Li, Shuyan Xiao, Maomao Zhang, and Xiaoguang Zhang, (2015) “Power Saving and Improving the Throughput of Spectrum Sharing in Wideband Cognitive Radio Networks”, Journal of Communications And Networks, 17, 4, 1229-2370.

[29] T. R. Arulselvi, T. Senthil Kumar, D. Devarajan and R. Lakshmi Rekha, (2016) “High Energy and Spectral Efficiency Analysis for Cognitive Radio Ad-Hoc Network Based Spectrum Aggregation”, International Journal of Advanced Research in Electronics and Communication Engineering (IJARECE) , 2278-909X.

[30] Vikramsinh Sawant, and Dimitrios Koutsonikolas, (2015) ‘Performance Comparison of Routing Protocols for Cognitive Radio Networks’, IEEE Transactions on Mobile Computing,14,6, 1536-1233.

[31] Wei Wang, et. al. (2015), “Joint spectrum sensing and access for stable dynamic spectrum aggregation”, EURASIP Journal on Wireless Communication and Networking.

[32] Wonju Lee, Jinkyu Kang, and Joonhyuk Kang, (2015) “Joint Resource Allocation for Throughput Enhancement in Cognitive Radio Femtocell Networks”, IEEE Wireless Communications Letters, 4, 2, 2162-2337.

[33] Xiaofeng Feng, Xinbo Gao, Ru Zong, (2017) “Cooperative Jamming for nhancing Security of Cognitive Radio Networks with Multiple Primary Users”, hina Communications ,1673-5447.

[34] Xiaoshi Song, Changchuan Yin, Danpu Liu, and Rui Zhang, (2014) “Spatial Throughput Characterization in Cognitive Radio Networks with Threshold-Based Opportunistic Spectrum Access”, IEEE Journal on Selected Areas in Communications, 32, 11, 0733-8716.

[35] Yogesh Kumar Sharma ,Takale D.G, Yogesh Kumar Sharma (2019), “A Review on Data Centric Routing for Wireless sensor Network”, JETIR,6,1,2349-5162.

[36] Yuanyi Wang, Xiaohui Zhao† and Hui Liang, (2018) “Throughput maximization-based optimal power allocation for energy-harvesting cognitive radio networks ith multiusers”, Wang et al. EURASIP Journal on Wireless Communications and Networking.

[37] Yunus Sarikaya, Ozgur Ercetin, Ozgur Gurbuz, (2018) “Control of Cognitive Networks with Friendly Jamming as a Service”, IEEE, 2332-7731.

[38] M. C. Grant, S. P. Boyd and Y. Ye, "CVX: Matlab software for disciplined convex programming (web page and software)," [Online]. Available: http://cvxr.com/cvx. [Accessed 14 04 2016].

[39] S. P. Boyd and Y. Ye, “Open Networking Foundation - OpenFlow,” [Online]. Available: https://www.opennetworking.org/sdn-resources/openflow. [Accessed 14 3 2016].